# 4850, 3-pole, Line Socket, solder terminal, DIN Plug/Socket









#### **Description**

- Solder terminal : for cable mounting
- DIN Plug: 3-pole , straight


#### **Technical Data**


| Diameter              | 9.0 mm            |  |  |
|-----------------------|-------------------|--|--|
| Number of Poles       | 3-pole            |  |  |
| Ratings DC            | 2A / 12VDC        |  |  |
| Ratings AC            | 1 A / 100 VAC     |  |  |
| Dielectric Strength   | 250 VAC           |  |  |
| Insulation Resistance | > 50 MΩ @ 250 VDC |  |  |
| •                     |                   |  |  |

| Allowable Operation Tempe- | -20°C to 70°C                 |  |
|----------------------------|-------------------------------|--|
| rature                     |                               |  |
| Terminal                   | solder terminal silver plated |  |
| Lifetime                   | 5000 Insertions               |  |
|                            |                               |  |

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in General Product Information

# **Dimensions**







# Cable diameter max. 5.0 mm

### **All Variants**

| Product group   | Diameter [mm] | Number of Poles | Terminal        | Order Number |
|-----------------|---------------|-----------------|-----------------|--------------|
| DIN Plug/Socket | 9.0           | 3-pole          | solder terminal | 4850.3300    |

A vailability for all products can be searched real-time: http://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

Packaging unit 100 Pcs

#### **Mating Inlets/Plugs**

Category / Description



**DIN Plug/Socket Overview complete** 

4850, 3-pole, Plug, solder terminal, DIN Plug/Socket

DIN Plug/Socket further types to 4850.3300

4850.1310