

13U SmartRack 2-Post Open Frame Rack - Organize and Secure Network Rack Equipment

MODEL NUMBER: SR2POST13



Highlights

- 13U 2-post open frame rack
- Black aluminum with 12-24 threaded and numbered mounting holes

Package Includes

- SR2POST13
- 28 pieces each of 12-24 screws and washers for equipment mounting
- Installation hardware
- Cable management hooks
- Warranty Information
- Owner's Manual

Description

Tripp Lite's SR2POST13 2-Post SmartRack Open Frame Rack is an economical way to accommodate 13U of rack space for 19-inch rackmount applications in limited spaces. Its heavy-duty, aluminum construction can safely support 800 lbs. of rackmount equipment. The black, textured powder coat finish makes it resistant to scratching while giving it a "classic," attractive appearance. The SR2POST13 is easy to install due to a self-squaring design combined with 12-24 threaded and numbered mounting positions along with bolt down provisions. Only standard hand tools are required for installation (9/16" wrench and 9/16" socket/ratchet). Multiple units can be bolted together side by side for easy expansion or customization as needed. The SR2POST13 2-Post SmartRack Open Frame Rack has been approved by EIA-310-D, IEC 60297-3-100, and RoHS, and is backed by a 5-year warranty.

Features

- Supports 800lbs of rackmount equipment
- Textured powder coat finish
- Heavy Duty Aluminum construction
- 12-24 threaded and numbered mounting positions
- Bolt down provisions
- Self squaring design
- Black finish
- Easy assembly

Specifications

| PHYSICAL | |
|----------------------------|--------|
| Rack Height (U Spaces) | 13 |
| Maximum Device Depth (in.) | 48 |
| Maximum Device Depth (cm) | 121.92 |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|-------------------------------------|---|
| Shipping Dimensions (hwd / in.) | 4.5 x 6.1 x 28 |
| Shipping Dimensions (hwd / cm) | 11.4 x 15.5 x 71.1 |
| Shipping Weight (lbs.) | 22.1 |
| Shipping Weight (kg) | 10.02 |
| Unit Dimensions (hwd / in.) | 28 x 20.3 x 4.75 |
| Unit Dimensions (hwd / cm) | 71.12 x 51.56 x 12.07 |
| Unit Weight (lbs.) | 20 |
| Unit Weight (kg) | 9.07 |
| Color | Black |
| Weight Capacity - Stationary (lbs.) | 800 |
| EIA Mounting Rails | 12-24 threaded and numbered vertical mounting rails |
| Weight Capacity - Stationary (kg) | 363 |
| Maximum Device Depth (mm) | 1219 |
| CERTIFICATIONS | |
| Approvals | EIA-310-D, IEC 60297-3-100, RoHS |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 5-year limited warranty |

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>