



## **REQUIRES CONTACT RETENTION WEDGE AWP-2P**





## NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

2. MODIFICATIONS: N/A

3. SPECIFICATIONS:

3.1 CURRENT RATING: 25 AMPS

3.2 OPERATING TEMPERATURE: -55°C TO +125°C

3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC. 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.

3.5 MOISTURE RESISTANCE: IP67 (MATED CONDITION)

3.6 MATING CYCLE DURABILITY: 100 CYCLES

3.7 RoHS COMPLIANT

4. MATING PART: ATP06-2S\* PLUG. ( \* = MODIFICATIONS AND COLORS )

5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.



CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL
SIZE	O.D.	O.D.	WIRE RANGE
12	3.40 mm (.134 in)	4.95 mm (.195 in)	10 - 14 AWG

PART NUMBER CHART				
COLOR	PART NUMBER			
GREY	ATP04-2P			
BLACK	ATP04-2P-BLK			

STANDARD MOLDED COLOR IS GREY. ADDITIONAL COLOR (BLACK) IS AVAILABLE VIA SPECIAL ORDER.

REVISIONS					
REV	ECO	DESCRIPTION	DATE	BY	APPR
А3	-	RELEASE NEW DWG FORMAT	18/OCT/13	DRP	-

RECEPTACLE, 2 PIN, ATP SERIES

ATP04-2P-XXX

