

Article Number: 115-06304

Releasable Cable Tie, Release Tab, 6.3" Long, 50 lb Tensile Strength, PA66, Natural, 1000/pkg Description:

Base Data		
	Local Order Number	RT50S9M4
	Туре	RT50S
	Color	Natural (NA)
	Features and benefits	<ul> <li>Special extended-pawl design offers a release feature for quick and easy access to wire bundles.</li> <li>Head design provides high tensile strength with very low insertion force even after repeated use.</li> <li>Bent tail ensures a quick and simple installation.</li> </ul>
	Quantity Per	bag
	Product Description	HellermannTyton Releasable Cable Ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.
	Short Description	Releasable Cable Tie, Release Tab, 6.3" Long, 50 lb Tensile Strength, PA66, Natural, 1000/pkg
Product Dimensions		
	Minimum Tensile Strength (Imperial)	50.0lbs
	Minimum Tensile Strength (Metric)	225.0N
	Length L (Imperial)	6.3"
	Length L (Metric)	160.0mm
	Fixation Method	None
	Identification Plate Position	none
	Releasable Closure	Yes
	Tie Closure	plastic pawl
	Variant	Inside Serrated
	Width W (Imperial)	0.18"
	Width W (Metric)	4.6mm
	Height H (Imperial)	0.06"
	Height H (Metric)	1.4mm

generated on: 4/29/2017

## 115-06304



Bundle Diameter Min. (Imperial)	0.06"
Bundle Diameter Min. (Metric)	1.5mm
Bundle Diameter Max. (Imperial)	1.38"
Bundle Diameter Max. (Metric)	35.0mm
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V2
Minimum Application Temperature	-
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes
Certification/Specification	UL
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number(Schedule B)	3926909987
Weight (Metric)	1.2kg
	Bundle Diameter Min. (Metric)  Bundle Diameter Max. (Imperial)  Bundle Diameter Max. (Metric)  Material  Material Shortcut  Flammability  Minimum Application Temperature  Operating Temperature  ROHS Compliant  Certification/Specification  UL Recognized (US and Canada)  Package Quantity (Imperial)  Package Quantity (Metric)  Customs Number(Schedule B)

generated on: 4/29/2017