




PANEL THICKNESS	X dimension
0.75-1.25 [0.030-0.049]	19.2-0.1 [7.56]
1.25-2.0 [0.049-0.079]	19.4-0.1 [7.64]
2.0-3.0 [0.079-0.118]	19.8-0.1 [7.80]

FIGS. 1




SWITCH FUNCTION	
POS. 1	POS. 2
DN	OFF
1-1a	OPEN



NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERMINAL NUMBERS FOR REF ONLY
4. RATING: 15A @ 125VAC OR
6A @ 250VAC
5. MATERIALS: TERMINALS: Silver Plated Copper Alloy
CONTACTS: Coin Silver, Silver Plated
6. ELECTRICAL LIFE: 10,000 cycles
7. CONTACT RESISTANCE: <20 Mega Ω
8. INSULATION RESISTANCE: >1000 Mega Ω
9. DIELECTRIC STRENGTH: >1500 V 1 minute
>3000 V between poles



E-SWITCH®

TITLE		R1966A BLK BLK EP	
REV.	ECN No.	DATE	CHKD
A	11664	9/19/01	CJB
DESCRIPTION		SCALE	DR
RELEASED FOR PRODUCTION		1.5:1	CJB
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED		DATE	DWG
		9/19/01	M301201
		REV	
			A