




APPLICABLE STANDARD				
 RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C <sup>(1) (2)</sup>	STORAGE TEMPERATURE RANGE	-10 °C TO 60 °C <sup>(3)</sup>
	VOLTAGE	60 V AC <sup>(5)</sup>	OPERATING HUMIDITY RANGE	RH 85 % MAX <sup>(2) (4)</sup>
	CURRENT	0.5 A <sup>(5)</sup>	STORAGE HUMIDITY RANGE	RH 70 % MAX <sup>(3) (4)</sup>
	APPLICABLE CABLE	AWG 36, 40 THIN COAXIAL CABLE		



### SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
<b>CONSTRUCTION</b>				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	x	x
MARKING	CONFIRMED VISUALLY.		x	x

	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
	2	DIS-F-004353	KN. SHIBUYA	HT. YAMAGUCHI	09. 12. 15

 REMARKS	APPROVED	HS. OKAWA	08. 05. 24	
	(1) INCLUDE TEMPERATURE RISE CAUSED BY CURRENT-CARRYING.	CHECKED	HT. YAMAGUCHI	08. 05. 24
	(2) OPERATING TEMPERATURE SHOULD BE -55 TO 40°C WHEN HUMIDITY EXCEEDS 80% RH.	DESIGNED	TS. SHIBUYA	08. 05. 24
	(3) THE SPECIFICATION IS APPLIED TO THE PRE-ASSEMBLED COMPONENT AND THE CABLE ASSEMBLED PRODUCT BOTH IN DELIVERY AND STORAGE, BEFORE ASSEMBLED TO PCB.	DRAWN	TS. SHIBUYA	08. 05. 24
	(4) THERE MUST NOT BE DEWFALL.			
(5) IT IS THE MAXIMUM VALUE OF CONNECTOR. CONFIRM THE SPECIFICATION OF THE CABLE.				

Unless otherwise specified, refer to JIS-C-5402.

Note	QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC4-158279-00	
	SPECIFICATION SHEET	PART NO.	FX16-21P-GNDL	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL575-3331-8-00	 1/1