

REV B:66

LENGTHWISE

REC.

AMP 1201 (10/69)

APPLICATOR PARTS LIST *SPLICE COMPL.*

NO.	PART	REQ	PART NO.	NO.	PART	REQ	PART NO.
1	WIRE CRIMPER 45644-3	1	37889	40	GUARD - Side 1-460582-2	1	372978
2	INS. CRIMPER	1	37889	41	Stripper Mount Bracket	1	372978
3	ANVIL	1	465315-1	42	Stripper Mount Bracket	1	372978
4	ANVIL SPACER			43	Spring-Slide 3/4 O.D.	1	2-24017-7
5	SHEAR BLADE	1	376894	44	Feed Plate Ret.	1	372998
6	STRIPPER PLATE-Feed	1	376905	45			
7	SHEAR BLADE SPACER			46			
8	FRONT SHEAR PLATE			47			
9	REAR ANVIL SPACER PLT.			48			
10	FRONT ANVIL SPACER PLT.			49			
11	TOOL SPACER			50			
12	CRIMP SPACER	1	370592	51			
13	FRONT STRIP GUIDE			52			
14	REAR STRIP GUIDE			53			
15	RAM	1	471057	55	SCREW SET SQ HD (DEP)	1	21077-7
16	TOOL HOLDER			56	NUT, HEX - JAM	1	22202-1
17	ADJ. CRIMP MOUNT ^{MS1} 465392-9	1	37889	57			
18	ADJ. BLOCK		37889	58			
19	APPLICATOR MOUNT ASSY.	1	473933	59			
20	BASE PLATE			60			
21	BASE BLOCK			61	LUBRICATOR ASS'Y	1	465184-R
22	STRIP GUIDE PLATE			62	TERMINAL LUBRICANT	REF	852931-2
23	ANVIL HOLDER	1	385941	63			
24	AUX. ANVIL HOLDER	1	378975	64	MOUNT BRACKET	≠	672978
25	STRIPPER	1	376945	65	TENSION ADJ. PLATE	1	374999
26	STRIPPER MOUNT			66			
27	RETAINER PLATE			67			
28	STRIPPER MOUNT BRACKET			68			
29	STRIPPER BUSHING			69	Note: Use Button Hd. Screws In		
30	STOCK DRAG	1	37889 -1	70	Items 2 and 18. No Washers		
31	STOCK DRAG WASHER NUT	1	21022-4	71	F REV PER ECN R176 7-14-74		
32	STOCK DRAG STUD	1	21015-8	72	G REV PER ECN 6-9832 6-25-73		
33	STOCK DRAG SPRING 23846-7	1	37889	73	D REV PER ECN 6-9633 4-4-73		
34	STOCK DRAG ADJ. SCREW	2	372997	74	C PER ECN 46782 FRNT-2-69		
35	FEED FINGER HOLDER				■ DENOTES WEARING PARTS		
36	FEED FINGER 811432-1	1	37889		● PURCHASE REPLACEMENTS		
37	FEED FINGER TIP			DESIGNED	R. Bennett 5-4-62		
38	FEED FINGER SPACER			CHECKED	N Tolmachev 5-4-62		
39	CRIMPING DATA PLATE	1	37889	APPROVED	D. D. Apple 5-4-62		

DATE DUE		TERMINALS	41197									
DATE SHIPPED		42627										
EXPLODED VIEW	A-6010-1 A-6010-2											
NOTES:	Adj Ins. Crimper											
CRIMP HEIGHT	<table border="1"> <tr><td></td><td></td><td rowspan="4">COMMON</td></tr> <tr><td></td><td></td></tr> <tr><td></td><td></td></tr> <tr><td></td><td></td></tr> </table>					COMMON						
		COMMON										
SERIAL NUMBER												
AMP-O-ELECTRIC	1-01273-3											
MECH FEED	672978											
Splice												
WIRE RANGE	3200-8200 GRA											
INS. RANGE	.100-.160											
ASSY. DWG.	673291-B	ALIGN. GAGE										
CRIMP	SIZE	TYPE	FEED									
WIRE	.110	F	.434									
INSUL.	.210	F										
SLEEVED												
CUSTOMER		DATE										
APPLICATOR PARTS LIST	A-671547-2	SHEET	3 OF 4									

NECA 2-2990 10-16-50 JES

L REV. PER ECN M8663-80 R3590 H-REV PER ECN R-4616 D486 7-27-82

BASE CASTING

570238

G REV ITEM (1) R792 in 10-10-74
H 40 MM ANVIL R1764 R3 5-31-76

J REV PER ECN R1764 R3 9-17-76
K ITEM 61-465184-2 WAS -1 R2251/10/76