


VIP-2/SC/FLK50/AB-1756

Order No.: 2322317

The figure shows a version with MODICON[®] TSX Quantum labeling



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2322317>

VARIOFACE COMPACT LINE, interface module for Allen-Bradley Controll-Logix, with Controll-Logix-specific labeling



Commercial data

GTIN (EAN)	4046356451000
sales group	I550
Pack	1 pcs.
Customs tariff	85369010
Weight/Piece	0.1994 KG
Catalog page information	Page 231 (IF-2009)

Product notes

WEEE/RoHS-compliant since:
06/03/2009



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data

Nominal voltage U_N	max. 60 V AC/DC
Max. current carrying capacity per branch	1 A
Number of positions	50
Width	95.9 mm

Height	65.5 mm
Depth	56 mm
Status display	No
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Mounting position	Any
Standards/regulations	IEC 60664
	DIN VDE 0109-11
Pollution degree	2
Surge voltage category	II

Connection data

Connection 1	Field level
Type of connection	Spring-cage connection
Number of positions	50
Conductor cross section solid min.	0.14 mm ²
Conductor cross section solid max.	1.5 mm ²
Conductor cross section stranded min.	0.14 mm ²
Conductor cross section stranded max.	1.5 mm ²
Conductor cross section AWG/kcmil min.	26
Conductor cross section AWG/kcmil max	14
Stripping length	6 mm
Connection 2	Control system level
Number of connections	1
Type of connection	Flat-ribbon cable plug connector in acc. with IEC 60603-13
Number of positions	50

Certificates / Approvals



Certification CUL, UL


CUL

Nominal voltage U_N	125 V
Nominal current I_N	1 A

AWG/kcmil	30-12
UL	
Nominal voltage U_N	125 V
Nominal current I_N	1 A
AWG/kcmil	30-12

Diagrams/Drawings

Circuit diagram



VIP-2/SC/FLK50/AB-1756 connection scheme

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;